

### PRODUCT FEATURES AND APPLICATIONS

---

#### Features

- 200µ White (both sides) PET film
- Can be perforated with various sizes, shapes or logos - please visit our website for more examples
- White (both sides)
- Bright smooth finish
- Corrosion free
- Excellent dimension stability
- Excellent lamination properties with EVA

#### Applications

Long-term interlayers laminated with EVA for architectural solutions in the glass industry, such as:

- Interior partitions
- Façades, ceilings, flooring, stairs
- Hotel lobbies
- Bathroom and kitchen applications
- Pilar covering
- Tables, furniture panels
- Luxury shops, shop counters and displays, shelves, stands
- Advertisement, Logos, Signage

### BENEFITS

---

- **State of the Art, world wide exclusive** perforation that allows almost every design, shapes or logos. Please visit our web site for more information.
- **Innovative:** will add amazing decorative features to any glass surface.
- **Unique Process** State of the art
- **Suitability** to different types of laminating processes (vacuum kiln and/or autoclave with vacuum-bags)
- **Durable** interior installations with excellent dimensional stability. Aging and durability tests for exterior are scheduled.
- **Easy cleaning** since embedded into glass (unexposed to cleaning agents and abrasion)
- **Same colour effect** on both sides.
- **European** made solution for better quality control and carbon footprint

### TECHNICAL INFORMATION

<ul style="list-style-type: none"><li>▪ <sup>2</sup>vacuum lamination recommended</li></ul>	Surface	2 sides 200 $\mu$ White perforated PET film
<ul style="list-style-type: none"><li>▪ value prior to lamination with EVA<sup>3</sup></li></ul>	Standard Width	1m
<ul style="list-style-type: none"><li>▪ if stored on vertical position (AA Zone 1)<sup>4</sup></li></ul>	Standard Length	25 ml
<ul style="list-style-type: none"><li>▪ For further information please contact us</li></ul>	Lamination processes with EVA <sup>2</sup>	Vacuum kiln, autoclave with vacuum-bags
Code: SP-White	Expected Lifetime	Not recommended
Roll size: 1mx15m	Exterior <sup>3</sup>	
	Storage	18 months if stored at 21° and 50% relative humidity
	Service Temperature Range	-40° C to 80°
	Storage Temperature	+10° C to 20° C
	Lamination temperature	Up to 130° C
	Dimensional Stability	Excellent

### WARRANTY

Information provided above is based upon tests that are believed to be reliable. They are intended as a source of information and do not constitute a warranty. Focal Design takes great pride in ensuring tight quality control and we warrant our products to be free from visible defects at the time of sale. Any material showing visual defect at the time of sale will be replaced without charge. Our liability is limited to the costs of material and Focal Design shall in no circumstances cover expenses associated to the transformation and/or application of its products.